

Auswahltabelle Fischbach D, DS

Typ	I max (A)	Volumenstrom VL [m³/h] bei $\rho = 1,2 \text{ kg/m}^3$, verfügbare statische Pressung Δp_{st} [Pa]																					
		frei	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1100	1200
D670/D500	2,6	3850	–	–	3690	3320	2886	2108	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
DS6-770/D1	4,8	5980	–	–	–	–	–	–	–	5790	5130	4240	–	–	–	–	–	–	–	–	–	–	–
D770/D1	5,43	6750	–	–	–	–	–	–	6730	6370	5900	5240	–	–	–	–	–	–	–	–	–	–	–
D970/D2	6,84	8480	–	–	–	–	8450	8200	7950	7635	7320	6875	6430	5540	4650	3290	1930	–	–	–	–	–	–
DS8-970/D2	6,75	7365	–	–	–	–	7201	6906	6611	6272	5933	5533	5133	4645	4157	3577	–	–	–	–	–	–	–
DS8-980/D2.5	10,95	10010	–	–	–	–	–	–	9925	9580	9250	8820	8395	7780	7165	5950	4740	–	–	–	–	–	–
DS9-070/D2.5	11	10250	–	–	–	–	–	–	–	–	–	–	9400	8995	8590	8060	7530	6755	5980	4860	3740	–	–
DS9-070/D5	17,81	12510	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	12510	11470	9850
DS9-001/D5	18,49	14360	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	14360	13335	12310	7435	2560
DS7-870/2xE65	13,07	7650	–	–	–	–	–	–	–	–	7630	7330	6980	–	6050	–	–	–	–	–	–	–	–
DS0-101/TD10	37,40	23020	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	22710	19980