

Auswahltablelle Helios Rohr- und Kanalventilatoren															
Typ	Schalldruck Abstrahlung L_{PA} dB(A) in 4 m Abst.	Schalldruck saugseitig L_{PA} dB(A) in 4 m Abst.	Volumenstrom V [m³/h] in Abhängigkeit vom statischen Druck (Δp_{st}) in Pa												
			0	50	100	150	200	250	300	350	400	500	600	700	800
KRW 180/2/30/15	37	51		540	480	420	360	280	210	110					
KRW 225/2/40/20	40	52	1020	920	820	700	590	490	380	260	100				
KRW 250/2/40/20	43	55	1480	1370	1260	1150	1050	950	840	730	610	380	90		
KRW 280/2/50/25	53	65	2360	2280	2210										
KRW 315/4/50/25	35	47	1600	1420	1230	1020	780	320	10						
KRW 315/2/50/25	43	54	1710	1620	1530	1430	1330	1220	1100	990	890	670	390		
KRW 355/4/50/25	43	56	2220	2060	1910	1730	1500	1230	920	470					
KRW 355/4/60/35	44	59	2990	2840	2700	2540	2350	2080	1760	1450	1030				
KRW 400/4/60/35	42	58	3900	3700	3490	3270	3040	2780	2510	2220	1890	480			
KRW 450/4/70/40	43	55	5300	5040	4780	4510	4210	3880	3510	3130	2750	1840	180		
KRD 450/4/70/40	46	57	5740	5480	5230	4970	4690	4410	4120	3820	3500	2800	1430		
KRD 500/4/80/50 A	48	59	7740	7460	7170	6880	6580	6270	5920	5550	5130	4080	2320		
KRD 500/4/80/50 B	51	62	9540	9270	9000	8720	8440	8150	7840	7510	7160	6350	5390	4120	960
KRW 560/6/100/50	46	56	10820	10280	9730	9140	8490	7730	6880	6000	5070	2640			
KRD 560/6/100/50	45	56	10710	10230	9750	9240	8690	8040	7280	6430	5500	2990			