

Auswahltablelle Helios Rohr- und Kanalventilatoren

Typ	Schalldruck Abstrahlung L_{PA} dB(A) in 4 m Abst.	Schalldruck saugseitig L_{PA} dB(A) in 4 m Abst.	Volumenstrom V [m³/h] in Abhängigkeit vom statischen Druck (Δp_{st}) in Pa												
			0	50	100	150	200	250	300	350	400	500	600	700	800
KVV 200/4/40/20	37	49	920	890	850	800	750	40	40	–	–	–	–	–	–
KVD 200/4/40/20	42	53	1490	1390	1290	1170	1030	910	–	–	–	–	–	–	–
KVV 225/4/50/25	43	54	–	–	1570	1480	1380	1250	1010	–	–	–	–	–	–
KVD 225/4/50/25	43	52	1920	1820	1710	1590	1460	1290	1040	–	–	–	–	–	–
KVV 250/4/50/30	42	57	–	–	–	2080	2000	1900	1770	1570	1200	–	–	–	–
KVD 250/4/50/30	42	56	–	–	–	2110	1970	1810	1610	1320	–	–	–	–	–
KVV 250/6/50/30	36	46	1760	1610	1440	1180	–	–	–	–	–	–	–	–	–
KVV 280/4/60/30	44	59	–	–	2810	2720	2620	2520	2410	2260	2050	–	–	–	–
KVD 280/4/60/30	45	60	3930	3780	3620	3470	3310	3150	2990	2820	2620	2000	–	–	–
KVV 280/6/60/30	37	49	–	2170	2040	1870	1580	–	–	–	–	–	–	–	–
KVD 280/6/60/30	35	49	–	–	–	1960	1620	–	–	–	–	–	–	–	–
KVV 315/4/60/35	47	59	–	–	–	–	–	–	3660	3550	3420	3030	1900	–	–
KVD 315/4/60/35	48	61	–	–	–	–	–	4400	4230	4060	3870	3430	2700	–	–
KVV 315/6/60/35	43	51	3490	3320	3140	2940	2700	2340	–	–	–	–	–	–	–
KVD 315/6/60/35	40	50	3800	3590	3370	3130	2850	2490	1750	–	–	–	–	–	–
KVD 355/4/70/40	54	67	–	–	–	–	–	–	5580	5440	5300	4960	4540	3920	–