

Auswahltabelle Helios Rohr- und Kanalventilatoren

Typ	Schalldruck Abstrahlung L_{PA} dB(A) in 4 m Abst.	Schalldruck saugseitig L_{PA} dB(A) in 4 m Abst.	Volumenstrom V [m ³ /h] in Abhängigkeit vom statischen Druck (Δp_{st}) in Pa												
			0	50	100	150	200	250	300	350	400	500	600	700	800
KVD 355/6/70/40	42	53	–	–	4970	4680	4380	4060	3680	3190	–	–	–	–	–
KVD 355/8/70/40	35	47	4790	4410	4000	3520	2850	–	–	–	–	–	–	–	–
KVD 400/4/80/50	55	66	–	–	–	–	–	–	–	–	–	–	–	–	–
KVD 400/6/80/50	45	60	7620	7320	7020	6710	6390	6060	5690	5290	4800	1460	–	–	–
KVD 400/8/80/50	38	51	–	–	5140	4670	4150	3420	–	–	–	–	–	–	–
KVD 450/6/100/50	50	60	–	–	–	–	–	–	8170	7850	7500	6630	5220	–	–
KVD 450/8/100/50	46	56	–	–	7290	6880	6420	5860	5120	3980	–	–	–	–	–